

T8 LED Frosted Tube (Direct AC)

ULT8025

USHIO

Features


- Material (Body) : Aluminium and PC Cover
- Lamp : SMD type LED
- Color Rendering : Ra 80
- Voltage : 85V - 265V AC, 50/60 Hz
- Dimmable : No
- Power Factor : >0.95
- Certification : CE Compliant
- Others : No Mercury / No UV / No IR

Equivalent FL Tube	IP rating IP40
LED Type SMD	LED Driver Built-in
Lifespan 40,000 Hours	Oper. Temp -20C°~ 45C°
PF 0.95	Base G13

System Power : 25W

Tube Length - 4ft

▲ 120°	ULT8025/30/03K/C0/F	25W	3000K	3000 lm
	ULT8025/40/03K/C0/F	25W	4000K	3100 lm
	ULT8025/60/03K/C0/F	25W	6000K	3100 lm



Dimension for 25W
L1 = 1213mm
L2 = 1198mm
Ø = 28mm

Wiring Diagram

Direct AC 110V - 240V with L and N at either side



Remove ballast and bypass direct as per above drawing

USHIO

■ USHIO ASIA PACIFIC PTE LTD
28 Genting Lane #05-05 Platinum 28, Singapore 349585
TEL +65 6274-5311 FAX +65 6274-5300
URL www.ushioasiapacific.com

■ USHIO ASIA PACIFIC (Thailand) LTD
Le Concorde Tower, Room 2006 (20F) 202 Rachadapisek Road, Huaykwang,
Bangkok 10310 Thailand
TEL +66 2 694-1440 FAX +66 2 694-1770
URL www.ushioasiapacific.com